CLAIMS

Therefore, having thus described the invention, at least the following is claimed:

- 1. An exhaust system for removing fumes from an endoscope disinfecting apparatus configured for disinfecting an endoscope with a disinfecting solution, said exhaust system comprising:
 - a fan housing;

1

2

3

6

2

3

4

1

2 🗒

1

2

1

2

1

2

3

Hand.

- a fan disposed within said fan housing;
- an exhaust hose connected to said fan housing; and
- wherein said exhaust system is connected to said endoscope disinfecting apparatus.
- The system of claim 1, wherein said endoscope disinfecting apparatus further includes a soaking basin and a basin lid, said lid being configured to contain fumes from the disinfecting solution within a vapor space defined by said lid, said soaking basin, and a surface of the disinfecting solution.
- 3. The system of claim 2, wherein said fan housing is connected to said soaking basin such that said fan is communicatively coupled to said vapor space.
- 4. The system of claim 3, wherein said fan removes said fumes from said vapor space and exhausts said fumes through said exhaust hose.
- The system of claim 2, wherein said fan housing is connected to said lid such that said fan is communicatively coupled to said vapor space.
- 6. The system of claim 2, wherein said exhaust system further includes a suction hose having a first end and a second end, said first end being connected to said soaking basin and said second end being connected to said fan housing such that said fan is communicatively coupled to said vapor space.

1

2

1

2

3

7.	The system of claim 2, wherein said exhaust system further includes a suction
hose having a	first end and a second end, said first end being connected to said lid and said
second end be	eing connected to said fan housing such that said fan is communicatively coupled to
said vapor spa	ace.

- The system of claim 2, wherein said exhaust system further includes a plurality of suction hoses and a plurality of endoscope disinfecting apparati, each of said plurality of suction houses communicatively coupling one of said plurality of endoscope disinfecting apparati with
- The system of claim 1, wherein said exhaust system further includes a motor for driving said fan, said motor being disposed within a motor housing, said motor housing being
 - The system of claim 1, wherein said fan is an electric fan.
- An exhaust system for removing fumes from an endoscope disinfecting apparatus configured for disinfecting an endoscope with a disinfecting solution, said exhaust system
- a fume hood to provide a vapor containment space over said endoscope disinfecting
- wherein said fan housing is communicatively coupled to said fume hood such that fumes can be removed from said vapor containment space by said exhaust system.
- The system of claim 11, wherein said fume housing further includes an access 12. door that permits access to said endoscope disinfecting apparatus for insertion and removal of the endoscope.

wherein said disinfecting basin is a well connected to a side of said endoscope body

insertion tube of the endoscope; and

7

8

9

section.

1	18.	The system of claim 11, wherein said endoscope disinfecting apparatus further					
2	comprises:						
3	a disinfecting basin that disinfects an air/water and light tube of the endoscope;						
4	an endoscope body section connected to said disinfecting basin that disinfects a body and						
5	eye piece of the endoscope; and						
6	an insertion tube section connected to said endoscope body section that disinfects an						
7	insertion tube of the endoscope, wherein said insertion tube section is coiled.						
		•					
1	19.	The system of claim 18, wherein said endoscope disinfecting apparatus further					
2	comprises a support cylinder and said insertion tube section is coiled around said support						
3 []	cylinder.						
l.,							
1	20.	The system of claim 18, wherein said insertion tube section is coiled between ½					
1 2 m m m m m m m m m m m m m m m m m m	and 5 turns.						
1	21.	An exhaust system for removing fumes from an endoscope disinfecting apparatus					
2 []	configured for disinfecting an endoscope with a disinfecting solution, said exhaust system						
	comprising:						
4	a fume hood to provide a vapor containment space over said endoscope disinfecting						
5	apparatus;						
6	a fan housing;						
7	a fan disposed within said fan housing;						
8	an exhaust hose connected to said fan housing; and						
9	wherein said fan housing is communicatively coupled to said fume hood such that fumes						
10	can be removed from said vapor containment space by said exhaust system, and wherein said						
11	endoscope disinfecting apparatus includes a support cylinder and an insertion tube section coiled						
12	around said support cylinder.						

1

2

3

4

5

	22.	An endoscope	disinfecting	apparatus	comprising:
--	-----	--------------	--------------	-----------	-------------

a disinfecting basin that disinfects an air/water and light tube of the endoscope;

an endoscope body section connected to said disinfecting basin that disinfects a body and eye piece of the endoscope; and

an insertion tube section connected to said endoscope body section that disinfects an insertion tube of the endoscope, wherein said insertion tube section is coiled.

- 23. The apparatus of claim 22, further comprising a support cylinder and wherein said insertion tube section is coiled around said support cylinder.
- 24. The apparatus of claim 23, further comprising a second endoscope disinfecting apparatus including a second insertion tube section coiled around said support cylinder.
- 25. The apparatus of claim 22, wherein a plurality of coils of said insertion tube section is formed such that each one of said plurality of coils contact each other.
- 26. The apparatus of claim 22, wherein a plurality of coils of said insertion tube section includes at least one support strut formed between adjacent of said plurality of coils.